

IN THE SPECIFICATION

Page 3, lines 1-4 has been amended as follows:

each of the pawl members is **[pivotally]** mounted in a respective one of the receiving recesses and has a first face formed with a toothed portion engaged with the toothed portion of the ratchet wheel, each of the pawl members has an end formed with a driven block;

Page 6, lines 3-8 has been amended as follows:

Each of the pawl members 30 is **[pivotally]** mounted in a respective one of the receiving recesses¹² of the body 10 and has two parallel sides 32. Each of the pawl members 30 has a first face formed with a toothed portion 31 engaged with the toothed portion 21 of the ratchet wheel 20 and a second face formed with a locking portion 34. Each of the pawl members 30 has an end formed with a driven block 33.

IN THE CLAIMS

Claim 1 (currently amended): A screwdriver, comprising a body, a ratchet wheel, two pawl members, two elastic members, a cover, and a catch plate, wherein:

the body has a first end formed with a receiving hole, **[and]** a plurality of receiving recesses **[each]** communicating with the receiving hole[, **the first end of the body is formed with]** **and** a positioning slit **in communication with the receiving recesses;**

the ratchet wheel is mounted on the body and has an outer wall formed with an annular toothed portion mounted in the receiving hole of the body;

each of the pawl members is **[pivotally]** mounted in a respective one